




→ Condensing units Refrigeration heat exchangers

UNITS	SPECIFICATIONS	MARKETS						APPLICATIONS	
		Industries	Offices	Hotels & Shopping centres	Healthcare	Residential	Airports		
DRY COOLERS - CONDENSERS									
NEW 	AEROCONNECT 1B		X	X	X	X		X	AEROCONNECT makes it possible to adjust to temperature or pressure, control operating parameters, communicate with CIAT chillers, and diagnose and store faults.
NEW 	AEROFRESH		X	X	X	X		X	AEROFRESH is an adiabatic water-spray cooling system whereby an ultrafine water mist is sprayed at pressures of up to 100 bar against a stream of air.
CONDENSING UNITS									
	Condenciat CL Cc: 5 to 19		X	X	X				Outdoor condensing unit for direct expansion applications Variable speed propeller fan
	Condenciat CD Cc: 25 to 165		X	X	X				Quiet operation Low speed fans All year round operation
REFRIGERATION HEAT EXCHANGERS									
	EXEL Brazed plate heat exchangers Cc and Hc: 1 to 200		X						Very economical to buy, install and operate, very compact and lightweight, fully welded construction Exceptional mechanical strength and zero leaks
	COREVA FYN - FYH Shell and tubes Dry expansion evaporator Cc: 50 to 3000		X						Corrugated tubes for enhanced heat transfer Refrigerant grade components range of optimised units

Cc = cooling capacity in kW

Hc = Heating capacity in kW

