





UNITS	SPECIFICATIONS	MARKETS						APPLICATIONS
		Industries	Offices	Hotels & Shopping centres	Healthcare	Residential	Airports	
<b>FLUID-TO-FLUID HEAT EXCHANGERS</b>								
<b>CORELIS Heat exchangers for district networks</b>								
		X	X	X			X	Unequaled reliability Maximal safety :superheated water circuitfully welded construction free expansion of the bundle Reduced and quick maintenance
<b>DOMESTIC WATER APPLICATIONS</b>								
<b>SANICAT MSC Domestic hot water production modules</b>								
	F: up to 12,3 m³/h		X	X	X			Packaged units for instantaneous and semi-instantaneous domestic hot water production Many options Electronic control Anti-legionella function included
<b>NEW</b>	<b>WATERCLEAN SYSTEM</b>							
	F: up to 9,5 m³/h			X	X			Instantaneous production and continuous thermal treatment of hot and cold water for domestic use Protects against the risk of legionella, pseudomonas and other bacteria.
<b>COMPONENTS FOR DEHUMIDIFYING BIOGAS</b>								
<b>NEW</b>	<b>BIOGAZ</b>							
	F: 100 to 6000 Nm³/hr	X						Motor protection/ Improved performance Optimised systems/ Increased component reliability 800 installations equipped worldwide

F = flow rate in m³/h

Hc: heating capacity in kW